

3DMASi

TRIS(DIMETHYLAMIDO)SILANE

Physical Properties

Vapor pressure equat.:	9.33 mbar at 20 °C / 17.33 mbar at 36 °C / 21.33 mbar at 40 °C
Density:	0.84 g/cm ³
Molweight:	161.32 g/mol
Melting point:	-90 °C / -130 °F
Boiling point:	145-148 °C / 293-298 °F
Sublimation point:	

Chemical Properties

Stability:	Stable under recommended storage conditions
State of matter:	Liquid

Safety & Transport

Toxicity:	n.a.
Thermal decomposition:	
ADR/RID-class:	4.3
UN-no:	3398
IMDG-class:	4,3
UN-no:	3398
ICAO/IATA-class:	4,3
UN-no:	3398 – AIRFREIGHT ALLOWED

For further details please refer to Safety Data Sheet (SDS)

Packaging & Standard Filling Volumes

3DMASi.100.DOCK/10.150	100g / 150ccm cyl.
3DMASi.290.DOCK/10.400	290g / 400ccm cyl.
3DMASi.425.DOCK/10.600	425g / 600ccm cyl.
3DMASi.725.DOCK/10.1000	725g / 1000ccm cyl
3DMASi.2100.DOCK/10.3000	2100g / 3000ccm cyl

Product Description

Name:	TRIS(DIMETHYLAMIDO)SILANE
CAS-Number:	15112-89-7
Element:	Si
Molecular Formula:	C ₆ H ₁₉ N ₃ Si

Quality Standards

EG Electronic Grade

Application

ALD and CVD precursor

Vapor Pressure

© 2024 Dockweiler Chemicals GmbH. All rights reserved. Version 07/2024. This data sheet is subject to change without notice. Despite careful checking and regular updating of the content, we accept no liability for the accuracy, completeness or currency of the information provided. Any liability, in particular for any damage or consequences arising from the use of the information provided, is excluded.

