

BTBMMo

BIS(TERT-BUTYLIMIDO)BIS(DIMETHYLAMIDO)MOLBYDENUM(VI)

Physical Properties

Vapor pressure equat.:	$\log(p(\text{Torr})) = 9.8 - 3447/T(\text{K})$
Density:	ca. 1.3 g/cm ³
Molweight:	326.35 g/mol
Melting point:	n.a.
Boiling point:	61 °C / 142 °F (0.027 mbar)
Sublimation point:	

Chemical Properties

Stability:	Stable under recommended storage conditions
State of matter:	Liquid

Safety & Transport

Toxicity:	n.a.
Thermal decomposition:	
ADR/RID-class:	4.3
UN-no:	3399, PG I
IMDG-class:	4,3
UN-no:	3399, PG I
ICAO/IATA-class:	4,3
UN-no:	3399, PG I - AIR FREIGHT ALLOWED

For further details please refer to Safety Data Sheet (SDS)

Packaging & Standard Filling Volumes

BTBMMo.100.DOCK/10.150	100g / 150ccm cyl.
BTBMMo.400.DOCK/10.400	400g / 400ccm cyl.
BTBMMo.600.DOCK/10.600	600g / 600ccm cyl.
BTBMMo.1000.DOCK/10.1000	1000g / 1000ccm cyl.
BTBMMo.3000.DOCK/10.3000	3000g / 3000ccm cyl.

Product Description

Name:	BIS(TERT-BUTYLIMIDO)BIS(DIMETHYLAMIDO)MOLBYDENUM(VI)
CAS-Number:	923956-62-1
Element:	Mo
Molecular Formula:	C ₁₂ H ₃₀ N ₄ Mo

Quality Standards

DG Development Grade

Application

ALD and CVD precursor

Vapor Pressure

Vapor Pressure
[mbar]

