

DMEAAI

DIMETHYLETHYLAMINE ALANE ADDUCT

Physical Properties

Vapor pressure equat.:	2.0 mbar at 25 °C
Density:	0.837 g/cm ³
Molweight:	103.14 g/mol
Melting point:	5 °C / 41 °F
Boiling point:	50 °C / 122 °F (0.067 mbar)
Sublimation point:	

Chemical Properties

Stability:	Stable under recommended storage conditions
State of matter:	Liquid

Safety & Transport

Toxicity:	Pyrophoric
Thermal decomposition:	
ADR/RID-class:	4.2(4.3)
UN-no:	3394, PG I
IMDG-class:	4.2(4.3)
UN-no:	3394, PG I
ICAO/IATA-class:	4.2(4.3)
UN-no:	3394, PG I – AIRFREIGHT FORBIDDEN

For further details please refer to Safety Data Sheet (SDS)

Packaging & Standard Filling Volumes

DMEAAI.100.DOCK/10.150	100g / 150ccm cyl.
DMEAAI.250.DOCK/10.400	250g / 400ccm cyl.
DMEAAI.400.DOCK/10.600	400g / 600ccm cyl.
DMEAAI.750.DOCK/10.1000	750g / 1000ccm cyl
DMEAAI.2000.DOCK/10.3000	2000g / 3000ccm cyl.

Product Description

Name:	DIMETHYLETHYLAMINE ALANE ADDUCT
CAS-Number:	124330-23-0
Element:	Al
Molecular Formula:	C ₄ H ₁₄ NAI

Quality Standards

EG Electronic Grade

Application

III/V MOCVD, ALD

Vapor Pressure

© 2024 Dockweiler Chemicals GmbH. All rights reserved. Version 07/2024. This data sheet is subject to change without notice. Despite careful checking and regular updating of the content, we accept no liability for the accuracy, completeness or currency of the information provided. Any liability, in particular for any damage or consequences arising from the use of the information provided, is excluded.

