

HMDSiK

HEXAMETHYLDISILAZANIDEPOTASSIUM

Physical Properties

Vapor pressure equat.:	<0.13 mbar at 25 °C
Density:	0.877 g/cm ³
Molweight:	199.48 g/mol
Melting point:	158-162 °C / 316.4-323.6°F
Boiling point:	n.a.
Sublimation point:	

Chemical Properties

Stability:	Stable under recommended storage conditions
State of matter:	Solid

Safety & Transport

Toxicity:	n.a.
Thermal decomposition:	
ADR/RID-class:	8, III
UN-no:	3263
IMDG-class:	8, III
UN-no:	3263
ICAO/IATA-class:	8, III
UN-no:	3263 – AIRFREIGHT ALLOWED

For further details please refer to Safety Data Sheet (SDS)

Packaging & Standard Filling Volumes

HMDSK.100.DOCK/10.150	100g / 150ccm cyl.
HMDSK.200.DOCK/10.400	200g / 400ccm cyl.
HMDSK.400.DOCK/10.600	400g / 600ccm cyl.
HMDSK.750.DOCK/10.1000	750g / 1000ccm cyl.
HMDSK.2000.DOCK/10.3000	2000g / 3000ccm cyl.

Product Description

Name:	HEXAMETHYLDISILAZANEPOTASSIUM SALT
CAS-Number:	40949-94-8
Element:	K
Molecular Formula:	C ₆ H ₁₈ NSi ₂ K

Quality Standards

DG Development Grade

Application

Potassium precursor for CVD and ALD applications

Vapor Pressure

© 2024 Dockweiler Chemicals GmbH. All rights reserved. Version 07/2024. This data sheet is subject to change without notice. Despite careful checking and regular updating of the content, we accept no liability for the accuracy, completeness or currency of the information provided. Any liability, in particular for any damage or consequences arising from the use of the information provided, is excluded.

